

# SAFETY DATA SHEET

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II



Product name: Rostprimer B38  
Date of printing: 14.11.2025

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

Product name: Rostprimer B38  
Unique Formula Identifier (UFI-Code): XG70-60V4-A006-DUVH  
Product type: alkyd primer

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Field of application: metal industry  
Identified uses: Industrial applications, Professional applications, Used by spraying.

### 1.3 Details of the supplier of the safety data sheet:

Producer/Supplier: Bisdorf GmbH  
Industriestraße 49-51  
D-52224 Stolberg  
  
Telephone: +49 (0) 2402 / 71048  
Telefax: +49 (0) 2402 / 75465  
E-Mail address: [bisdorf-lacke@arcor.de](mailto:bisdorf-lacke@arcor.de)

### 1.4 Emergency telephone number

Emergency information: Information Center against Poisons  
University Bonn  
Telephone number: +49 (0)228 / 19240  
  
Date of issue: 14.11.2025  
Date of previous issue: 18.10.2023

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

Product definition: Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

| Classification acc. to GHS |                                                                                 |                           |                  |
|----------------------------|---------------------------------------------------------------------------------|---------------------------|------------------|
| Section                    | Hazard class                                                                    | Hazard class and category | Hazard statement |
| 2.6                        | flammable liquid                                                                | Flam. Liq. 3              | H226             |
| 3.2                        | skin corrosion/irritation                                                       | Skin Irrit. 2             | H315             |
| 3.8D                       | specific target organ toxicity - single exposure (narcotic effects, drowsiness) | STOT SE 3                 | H336             |

See Section 11 for more detailed information on health effects and symptoms.

# SAFETY DATA SHEET

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II



Product name: Rostprimer B38  
Date of printing: 14.11.2025

## 2.2 Label elements

Hazard pictograms:



Signal word: Warning

Hazard statements:  
H226 - Flammable liquid and vapor.  
H315 - Causes skin irritation.  
H336 - May cause drowsiness or dizziness.  
EUH066 - Repeated exposure may cause skin dryness or cracking.

Precautionary statements:

Prevention:  
P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
P260 - Do not breathe dust/ fume/ gas/ mist/ vapors/ spray.  
P271 - Use only outdoors or in a well-ventilated area.  
P280 - Wear protective gloves/protective clothing/eye protection/face protection.

Response:  
P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.  
P303 + P361 + P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.  
P304 + P340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing  
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P314 - Get medical advice/attention if you feel unwell.  
P331 - Do NOT induce vomiting.  
Storage:  
P403 + P233 - Store in a well-ventilated place. Keep container tightly closed.  
P403 + P235 - Store in a well-ventilated place. Keep cool.  
P405 - Store locked up.  
Disposal:  
P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

Supplemental label elements: -

Indication at Labelling:

The pictogram GHS 02 (flame) can according GHS/CLP Art. 33 (3) substituted to label of ADR.

## 2.3 Other hazards

Endocrine disrupting properties (human health):

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Endocrine disrupting properties (environment):

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

PBT and vPvB assessment:

This substance/mixture contains components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB).

# SAFETY DATA SHEET

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II



Product name: Rostprimer B38  
Date of printing: 14.11.2025

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

| Product/ingredient name                                                     | Identifiers                                                                                   | %    | Classification<br>1272/2008/EC (CLP)                                                                                                                                         | Type    |
|-----------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------|------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------|
| xylene (mixture of isomers)                                                 | REACH: 01-2119488216-32<br>CAS: 1330-20-7<br>EG: 215-535-7                                    | 5-10 | Flam. Liq. 3, H226<br>Acute Tox. 4, H312<br>Acute Tox. 4, H332<br>Asp. Tox. 1, H304<br>Skin Irrit. 2, H315<br>Eye Irrit. 2, H319<br>STOT SE 3, H335<br>STOT RE 2, H373       | [1] [2] |
| ethylbenzene                                                                | REACH: 01-2119489370-35<br>CAS: 100-41-4<br>EG: 202-849-4                                     | 1-5  | Flam. Liq. 2, H225<br>Asp. Tox. 1, H304<br>Acute Tox. 4, H332<br>STOT SE 3, H335<br>STOT RE 2, H373 (hearing organs)                                                         | [1] [2] |
| solvent naphtha<br>(petroleum), light arom.                                 | REACH: 01-2119455851-35<br>CAS: *64742-95-6<br>EG: 265-199-0<br>M-Faktor: 1                   | 5-10 | Flam. Liq. 3, H226<br>Asp. Tox. 1, H304<br>STOT SE 3, H335<br>STOT SE 3, H336<br>Aquatic Chronic 2, H411                                                                     | [1] [2] |
| hydrocarbons, C9-C11, n-<br>alkanes, isoalkanes,<br>cyclics, < 2% aromatics | REACH: 01-2119463258-33<br>CAS: 64742-48-9<br>EG: 265-150-3                                   | 5-10 | Flam. Liq. 3, H226<br>Asp. Tox. 1, H304<br>STOT SE 3, H336                                                                                                                   | [1] [2] |
| 2-pentanone oxime                                                           | REACH: 01-2119980079-27<br>CAS: 623-40-5<br>EG: 484-470-6                                     | <0,5 | AcuteTox. 4, H302<br>Eye Irrit. 2, H319                                                                                                                                      |         |
| trizinc bis(orthophosphate)                                                 | REACH:<br>01-2119485040-44 (90%)<br>01-2119490076-36 (10%)<br>CAS: 7779-90-0<br>EG: 231-944-3 | <5   | Mixture containing 90% of Zinc<br>Phosphate and 10% of a non<br>hazardous additive.<br>This Mixture is not subjected to<br>classification and labelling (see<br>chapter 12). | [2]     |

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

#### Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

# SAFETY DATA SHEET

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II



Product name: Rostprimer B38  
Date of printing: 14.11.2025

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

**General information:** In all cases of doubt, or when symptoms persist, seek medical attention. If unconscious, place in recovery position and get medical attention immediately. Never give anything by mouth to an unconscious person. In any case show the physician the Safety Data Sheet.

**Inhalation:** Remove affected persons from dangerous area by observing suitable respiratory Protection measures. Remove the casualty into fresh air and keep at rest. After intensive inhalation consult a doctor in every case, even if no symptoms occur.

**Skin contact:** Take off immediately all contaminated clothing. Wash contaminated clothing before reusing. Do not allow the product to dry on the skin. Wash skin thoroughly with soap and water or use recognised skin cleanser. Consult a doctor in case of persisting skin irritation.

**Eye contact:** Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Begin with medical treatment.

**Ingestion:** If swallowed, rinse mouth with water (only if the person is conscious). Do not induce vomiting unless directed to do so by medical personnel. Seek medical attention.

### 4.2 Most important symptoms and effects, both acute and delayed

**General information:** When inhaled or swallowed depending on the time and amount, it can give rise to the following symptoms: headaches, giddiness, tiredness, nausea, vomiting, irregular heart beat, intoxication, unconsciousness, asphyxiation and fatality.

### 4.3 Indication of any immediate medical attention and special treatment needed

**Notes to physician:** Symptomatic treatment.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media



**Suitable:** Extinguishing measures to suit surroundings. In case of fire, use water spray jet, dry extinguishing powder, foam or carbon dioxide.

**Not suitable:** water jet.

### 5.2 Special hazards arising from the substance or mixture

**Hazardous combustion**

**Products:** Fire will produce dense black smoke containing hazardous combustion products. In a fire, the following may be released: carbon dioxide, carbon monoxide, not combusted hydrocarbons.

### 5.3 Advice for firefighters

**Special protective equipment for fire-fighters:** During fire-fighting wear self-contained breathing apparatus and protective clothing.

**Additional information:** The product is flammable. Use water spray to keep fire-exposed containers cool. Use extinguishing media suitable for surrounding materials. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

# SAFETY DATA SHEET

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II



Product name: Rostprimer B38  
Date of printing: 14.11.2025

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

General information: To avoid fire, eliminate ignition sources. Provide adequate ventilation. Use personal protective equipment. Avoid contact with eyes, skin and clothing. Avoid breathing vapours, spray or mists.

### 6.2 Environmental precautions

General information: Do not discharge into the drains / surface waters / groundwater. Prevent spread over a wide area e.g. by containment or oil barriers.

### 6.3 Methods and material for containment and cleaning up

General information: Absorb with liquid-binding material (sand, diatomite, universal binders etc.) or use a spill kit. Containers in which spilt substance has been collected must be adequately labelled. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

### 6.4 Reference to other sections

General information: See Section 1 for emergency contact information.  
See Section 8 for information on appropriate personal protective equipment.  
See Section 13 for additional waste treatment information.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Protective measures: Keep away from sources of ignition - No smoking. Vapours may form explosive mixtures with air.  
Take precautionary measures against electrostatic discharges. Provide good ventilation of working area. The working procedure should be planned as far as allowed by state-of-the-art technology so as to avoid release of hazardous substances or prevent skin contact. The level of risk involved in product handling must be reduced to a minimum by means of protective and preventive measures.

### 7.2 Conditions for safe storage, including any incompatibilities

General information: Store in a dry, cool and well-ventilated area. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. Store in accordance with local regulations.

German storage class: 10 - Combustible liquids neither in Storage Class 3

### 7.3 Specific end use(s)

See separate Product Data Sheet for recommendations or industrial sector specific solutions.

# SAFETY DATA SHEET

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II



Product name: Rostprimer B38  
Date of printing: 14.11.2025

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational exposure limit values (Workplace Exposure Limits)

| Product/ingredient name                                              | CAS-Nr.    | Notation | Identifier | TWA [ppm] | TWA [mg/m³] | STEL [ppm] | STEL [mg/m³] | Source      |
|----------------------------------------------------------------------|------------|----------|------------|-----------|-------------|------------|--------------|-------------|
| xylene (mixture of isomers)                                          | 1330-20-7  | skin     | IOELV      | 50        | 221         | 100        | 442          | 2017/164/EU |
| ethylbenzene                                                         | 100-41-4   | skin     | IOELV      | 100       | 442         | 200        | 884          | 2017/164/EU |
| solvent naphtha (petroleum), light arom.                             | 64742-95-6 |          | IOLEV      | 25        | 120         |            |              | 2017/164/EU |
| hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics | 64742-48-9 |          |            | 25        | 125         |            |              | AGCIH       |
| trizinc bis(orthophosphate)                                          | 7779-90-0  |          | IOLEV      |           | 10          |            |              | 2017/164/EU |

#### Notation

STEL Short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period unless otherwise specified

TWA Time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average

#### DNELs/DMELs

| Product/ingredient name     |                   |                                                 |
|-----------------------------|-------------------|-------------------------------------------------|
| xylene (mixture of isomers) |                   |                                                 |
| Oral                        | DNEL (population) | 1,6 mg/kg bw/day (Long-term - systemic effects) |
| Dermal                      | DNEL (worker)     | 180 mg/kg bw/day (Long-term - systemic effects) |
|                             | DNEL (population) | 108 mg/kg bw/day (Long-term - systemic effects) |
| Inhalation                  | DNEL (worker)     | 77 mg/m³ (Long-term - systemic effects)         |
|                             |                   | 289 mg/m³ (Acute - systemic and local effects)  |
|                             | DNEL (population) | 14,8 mg/m³ (Long-term - systemic effects)       |
|                             |                   | 174 mg/m³ (Acute - systemic and local effects)  |

| Product/ingredient name |               |                                                 |
|-------------------------|---------------|-------------------------------------------------|
| ethylbenzene            |               |                                                 |
| Dermal                  | DNEL (worker) | 180 mg/kg bw/day (Long-term - systemic effects) |
| Inhalation              | DNEL (worker) | 77 mg/m³ (Long-term - systemic effects)         |
|                         |               | 289 mg/m³ (Acute - systemic and local effects)  |

| Product/ingredient name                  |                   |                                                |
|------------------------------------------|-------------------|------------------------------------------------|
| solvent naphtha (petroleum), light arom. |                   |                                                |
| Oral                                     | DNEL (population) | 11 mg/kg bw/day (Long-term - systemic effects) |
| Dermal                                   | DNEL (worker)     | 25 mg/kg bw/day (Long-term - systemic effects) |
|                                          | DNEL (population) | 11 mg/kg bw/day (Long-term - systemic effects) |
| Inhalation                               | DNEL (worker)     | 150 mg/m³ (Long-term - systemic effects)       |
|                                          | DNEL (population) | 32 mg/m³ (Long-term - systemic effects)        |

# SAFETY DATA SHEET

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II



Product name: Rostprimer B38  
Date of printing: 14.11.2025

| Product/ingredient name                                              |                   |                                                             |
|----------------------------------------------------------------------|-------------------|-------------------------------------------------------------|
| hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics |                   |                                                             |
| Oral                                                                 | DNEL (population) | 300 mg/kg bw/day (Long-term - systemic effects)             |
| Dermal                                                               | DNEL (worker)     | 300 mg/kg bw/day (Long-term - systemic effects)             |
| Inhalation                                                           | DNEL (population) | 300 mg/kg bw/day (Long-term - systemic effects)             |
|                                                                      | DNEL (worker)     | 1500 mg/m <sup>3</sup> (Long-term - systemic effects)       |
|                                                                      | DNEL (population) | 900 mg/m <sup>3</sup> (Long-term - systemic effects) (24 h) |

| Product/ingredient name |                   |                                                       |
|-------------------------|-------------------|-------------------------------------------------------|
| 2-pentanone oxime       |                   |                                                       |
| Oral                    | DNEL (population) | 0,125 mg/kg bw/day (Long-term - systemic effects)     |
| Dermal                  | DNEL (worker)     | 0,375 mg/kg bw/day (Short-term - systemic effects)    |
|                         |                   | 0,208 mg/kg bw/day (Long-term - systemic effects)     |
|                         |                   | 0,624 mg/kg bw/day (Short-term - systemic effects)    |
| Inhalation              | DNEL (population) | 0,125 mg/kg bw/day (Long-term - systemic effects)     |
|                         | DNEL (worker)     | 24,9 mg/m <sup>3</sup> (Acute - local effects)        |
|                         | DNEL (population) | 8,3 mg/m <sup>3</sup> (Long-term - systemic effects)  |
|                         |                   | 2,07 mg/m <sup>3</sup> (Long-term - systemic effects) |

| Product/ingredient name     |               |                                                    |
|-----------------------------|---------------|----------------------------------------------------|
| trizinc bis(orthophosphate) |               |                                                    |
| Inhalation                  | DNEL (worker) | 5 mg/m <sup>3</sup> (Long-term - systemic effects) |

## PNECs

| Product/ingredient name     |                                                                  |
|-----------------------------|------------------------------------------------------------------|
| xylene (mixture of isomers) |                                                                  |
| PNEC aqua                   | 0,327 mg/l (fresh water)<br>0,327 mg/l (marine water)            |
| PNEC                        | 6,58 mg/l (STP (sewage treatment plant))<br>2,31 mg/kg dw (soil) |
| PNEC sediment               | 12,46 mg/kg dw (fresh water)<br>12,46 mg/kg dw (marine water)    |

| Product/ingredient name |                                                                  |
|-------------------------|------------------------------------------------------------------|
| ethylbenzole            |                                                                  |
| PNEC aqua               | 0,1 mg/l (fresh water)<br>0,01 mg/l (marine water)               |
| PNEC                    | 6,58 mg/l (STP (sewage treatment plant))<br>2,68 mg/kg dw (soil) |
| PNEC sediment           | 13,7 mg/kg dw (fresh water)<br>1,37 mg/kg dw (marine water)      |

# SAFETY DATA SHEET

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II



Product name: Rostprimer B38  
Date of printing: 14.11.2025

| Product/ingredient name     |                                                                   |
|-----------------------------|-------------------------------------------------------------------|
| trizinc bis(orthophosphate) |                                                                   |
| PNEC aqua                   | 20,6 µg/l (fresh water)<br>6,1 µg/l (marine water)                |
| PNEC                        | 52 µg/l (STP (sewage treatment plant))<br>106,8 mg/kg dw (soil)   |
| PNEC sediment               | 235,6 mg/kg mg/kg dw (fresh water)<br>113 mg/kg dw (marine water) |

(CAS 64742-95-6, 64742-48-9) - Substance is a hydrocarbon with a complex, unknown or variable composition. Conventional methods of deriving. PNECs are not appropriate and it is not possible to identify a single representative PNEC for such substances.

## 8.2 Exposure controls / personal protection

### Engineering measures

Refer to protective measures listed in sections 7.

### Personal protective equipment:

#### Respiratory protection

Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If working areas have insufficient ventilation: When the product is applied by means that will not generate an aerosol such as, brush or roller wear half or totally covering mask equipped with gas filter of type A, when grinding use particle filter of type P. Be sure to use approved/certified respirator or equivalent.

#### Hand protection

If there is a potential for product skin contact, use of gloves tested to e.g. EN 374 will provide sufficient protection. Protective gloves should in any case be tested for workplace-specific suitability (e.g. mechanical resistance, product compatibility, antistatic properties). Comply with instructions and information provided by the glove manufacturer concerning use, care and replacement of the gloves. Replace protective gloves immediately upon damage or at the first signs of wear. As far as possible, plan work procedures so that wearing gloves will not be necessary.

|                                      | Long term exposure | Short term exposure |
|--------------------------------------|--------------------|---------------------|
| Recommended gloves should be made of | Viton®             | Nitril.             |
| Material thickness                   | >0,7 mm            | >0,4 mm             |
| Permeation time                      | >480 min           | >480 min            |

#### Eye protection

Safety goggles with lateral shielding (DIN EN 166)

#### Body protection

Usual working clothes for the chemical industry, suitable for the job.

### Environmental exposure controls:

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

# SAFETY DATA SHEET

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II



Product name: Rostprimer B38  
Date of printing: 14.11.2025

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

#### Appearance

Physical state: Fluid

Colour: red-brown approx. RAL 3009; green approx. RAL 6011;  
gray approx. RAL 7001; light gray approx. RAL 7032;  
light gray approx. RAL 7035; light gray approx. RAL 7044;  
silver approx. RAL 9007, white approx. RAL 9002; white  
approx. RAL 9010; black approx. RAL 9005 and other colors

Odor: Characteristic

Odor threshold: Not relevant for the hazard classification of the product.

#### Security-relevant basic data

| Parameter                                                         |                                                                                           |
|-------------------------------------------------------------------|-------------------------------------------------------------------------------------------|
| pH-value                                                          | Not applicable.                                                                           |
| Melting point/Melting range                                       | <-50 °C                                                                                   |
| Boiling point/Boiling range                                       | 135 °C                                                                                    |
| Flash point                                                       | ~23-27 °C (IP 170 (ABEL))                                                                 |
| Flammability (solid / gas)                                        | Not applicable.                                                                           |
| Ignition temperature                                              | ~460 °C (lowest value of the individual components)                                       |
| Decomposition temperature                                         | Not determined.                                                                           |
| Auto-ignition temperature                                         | The product is not self-igniting.                                                         |
| Explosive properties                                              | Product is not explosive. However, formation of explosive air/steam mixtures as possible. |
| Explosion limits<br>Lower<br>Upper<br>Oxidizing properties        | 1,1 %(Vol)<br>6,6 %(Vol)<br>Not determined                                                |
| Vapour pressure                                                   | 10 hPa (20 °C)                                                                            |
| Density                                                           | ~1,46 g/cm <sup>3</sup> (20 °C)                                                           |
| Vapor density                                                     | Not determined                                                                            |
| Evaporation rate                                                  | No data available.                                                                        |
| Solubility in<br>Miscibility with water                           | Organic solvents (see point 3)<br>0.175 g/l                                               |
| Partition coefficient: (n-octanol/water)                          | Testing not relevant or not possible due to nature of the product.                        |
| Viscosity (expiry time after DIN 53211)<br>Dynamic:<br>Kinematic: | ~160 s DIN 4mm (20°C)                                                                     |
| Solvent separation test                                           | < 3% (20°C)                                                                               |

### 9.2. Other information

No additional information.

# SAFETY DATA SHEET

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II



Product name: Rostprimer B38  
Date of printing: 14.11.2025

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

General information: No specific test data related to reactivity available for this product or its ingredients.

### 10.2 Chemical stability

General information: The product is stable.

### 10.3 Possibility of hazardous reactions

General information: Rubber and other synthetic material can be affected.

### 10.4 Conditions to avoid

General information: The product is flammable. Keep away from excessive heat, sparks or open fire.

### 10.5 Incompatible materials

General information: oxidising agents, acids

### 10.6 Hazardous decomposition products

General information: Thermal disintegration depends to a great extent on the external conditions. A complex mixture of solids, liquids and gases forms in the air, including among other substances carbon dioxide, carbon monoxide and other organic compounds, when this material is burnt or is thermally or oxidatively degraded.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

| Product/ingredient name                                              | Result                 | Species | Dose                    | Exposure |
|----------------------------------------------------------------------|------------------------|---------|-------------------------|----------|
| xylene (mixture of isomers)                                          | LC50 Inhalation Gas    | Rat     | 5000 ppm                | 4 hours  |
|                                                                      | LC50 Inhalation Vapour | Rat     | 6350 ppm                | 4 hours  |
|                                                                      | LD50 Dermal            | Rabbit  | >5000 mg/kg             | -        |
| ethylbenzene                                                         | LD50 Oral              | Rat     | 4300 mg/kg              | -        |
|                                                                      | LC50 Inhalation Vapour | Rat     | 17,2 mg/l               | 4 hours  |
|                                                                      | LD50 Dermal            | Rabbit  | >5000 mg/kg             | -        |
| solvent naphtha (petroleum), light arom.                             | LD50 Oral              | Rat     | 3500 mg/kg              | -        |
|                                                                      | LC50 Inhalation Vapour | Rat     | >6153 mg/m <sup>3</sup> | 4 hours  |
|                                                                      | LD50 Dermal            | Rabbit  | >3160 mg/kg             | -        |
| hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics | LD50 Oral              | Rat     | 8400 mg/kg              | -        |
|                                                                      | LC50 Inhalation Vapour | Rat     | 8000 mg/kg              | 4 hours  |
|                                                                      | LD50 Dermal            | Rabbit  | >5000 mg/kg             | -        |
| 2-pentanone oxime                                                    | LD50 Oral              | Rat     | >5000 mg/kg             | -        |
| trizinc bis(orthophosphate)                                          | LD50 Oral              | Rat     | 1133 mg/kg              | -        |
|                                                                      | LD50 Oral              | Rat     | >5000 mg/kg             | -        |

### Acute toxicity estimates

| Route               | ATE-Value  |
|---------------------|------------|
| Dermal              | 1382 mg/kg |
| Inhalation (vapors) | 11.2 mg/l  |

### Corrosion/Irritation

| Product/ingredient name                  | Result                      | Species | Score | Exposure                |
|------------------------------------------|-----------------------------|---------|-------|-------------------------|
| xylene (mixture of isomers)              | Eyes - Severe irritant      | Rabbit  | -     | 24 hours 5 milligrams   |
|                                          | Skin - Moderate irritant    | Rabbit  | -     | 24 hours 500 milligrams |
| ethylbenzene                             | Skin - Mild irritant        | Rabbit  | -     | 24 hours 15 milligrams  |
|                                          | Respiratory - Mild irritant | Rabbit  | -     | -                       |
| solvent naphtha (petroleum), light arom. | Eyes - Mild irritant        | Rabbit  | -     | -                       |

# SAFETY DATA SHEET

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II



Product name: Rostprimer B38

Date of printing: 14.11.2025

| Product/ingredient name                                              | Result                                    | Species | Score | Exposure |
|----------------------------------------------------------------------|-------------------------------------------|---------|-------|----------|
| hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics | No irritant (according to EU directives). |         |       |          |

## Sensitiser

Remarks

Skin: No evidence of sensitizing effects.

Respiratory: May cause respiratory irritation.

## Mutagenicity

Remarks: No evidence of mutagenic effects.

## Carcinogenicity

Remarks: No evidence of carcinogenic effects.

## Reproductive toxicity

Remarks: No evidence that the substance is toxic for reproduction.

## Teratogenicity

Remarks: No evidence that the substance may cause birth defects.

## Specific target organ toxicity (single exposure)

| Product/ingredient name                                              | Category   | Route of exposure | Target organs                   |
|----------------------------------------------------------------------|------------|-------------------|---------------------------------|
| xylene (mixture of isomers)                                          | Category 3 | Not applicable.   | Respiratory tract<br>Irritation |
| solvent naphtha (petroleum), light arom.                             | Category 3 | Not applicable.   | Narcotic effects                |
| hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics | Category 3 | Not applicable.   | Narcotic effects                |

## Specific target organ toxicity (repeated exposure)

| Product/ingredient name                                              | Category   | Route of exposure | Target organs  |
|----------------------------------------------------------------------|------------|-------------------|----------------|
| xylene (mixture of isomers)                                          | Category 2 | Not determined    | Hearing organs |
| ethylbenzene                                                         | Category 2 | Not determined    | Hearing organs |
| hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics | Category 1 | Not determined    | Not determined |

## Aspiration hazard

| Product/ingredient name                                              | Result                         |
|----------------------------------------------------------------------|--------------------------------|
| xylene (mixture of isomers)                                          | ASPIRATION HAZARD - Category 1 |
| ethylbenzene                                                         | ASPIRATION HAZARD - Category 1 |
| solvent naphtha (petroleum), light arom.                             | ASPIRATION HAZARD - Category 1 |
| hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics | ASPIRATION HAZARD - Category 1 |

## Information on the likely routes of exposure

Routes of entry anticipated: Oral, Dermal, Inhalation.

## Potential chronic health effects

Remarks: Not available.

## 11.2 Endocrine disrupting properties

See Section 2 for details.

## 11.3 Other hazards

The product is flammable. Keep away from excessive heat, sparks or open fire. In use, may form flammable/explosive vapour/air mixture. Electrostatic charges may be generated during pumping, release of which may cause a fire. The vapour/gas is heavier than air and will spread along the ground. Vapour may travel a considerable distance to source of ignition and flash back. Aspiration hazard if swallowed. Can enter lungs and cause damage.

# SAFETY DATA SHEET

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II



Product name: Rostprimer B38

Date of printing: 14.11.2025

## SECTION 12: Ecological information

### 12.1 Toxicity

| Product/ingredient name                                              | Result                                                                                         | Species                                                                                                                    | Exposure                                     |
|----------------------------------------------------------------------|------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------|----------------------------------------------|
| xylene (mixture of isomers)                                          | Acute EC50 3,82 mg/l<br>Acute EC50 4,7 mg/l                                                    | Daphnie - Daphnia magna<br>Algae- Pseudokirchneriella subcapitata                                                          | 48 hours<br>72 hours                         |
| ethylbenzene                                                         | Acute LC50 7,6 mg/l<br>Acute EC50 2,4 mg/l<br>Acute EC50 4,6 mg/l                              | Fish - Oncorhynchus mykiss<br>Daphnie - Daphnia magna<br>Algae - Pseudokirchneriella subcapitata                           | 96 hours<br>48 hours<br>72 hours             |
| solvent naphtha (petroleum), light arom.                             | Acute EC50 3,2 mg/l<br>Acute EC50 19 mg/l                                                      | Fish - Oncorhynchus mykiss<br>Daphnie - Daphnia magna<br>Algae - Pseudokirchneriella subcapitata                           | 96 hours<br>48 hours<br>72 hours             |
| hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics | Acute LC50 9.22 mg/l<br>Acute EC50 >1000 mg/l<br>Acute IC50 >1000 mg/l                         | Fish - Oncorhynchus mykiss<br>Daphnie - Daphnia magna<br>Algae - Pseudokirchneriella subcapitata                           | 96 hours<br>48 hours<br>72 hours             |
| 2-pentanone oxime                                                    | Acute LC50 >1000 mg/l<br>Chronic NOEC 0,097 mg/l<br>Acute EC50 >100 mg/l<br>Acute EC50 88 mg/l | Fish - Oncorhynchus mykiss<br>Daphnie - Daphnia magna<br>Daphnie - Daphnia magna<br>Algae - Desmodesmus subspicatus        | 96 hours<br>21 days<br>48 hours<br>72 hours  |
| trizinc bis(orthophosphate)                                          | Acute LC50 >100 mg/l<br>NOEC >100 mg/l<br>Acute EC50 >100 mg/l*<br>Acute EC50 >100 mg/l*       | Fish - Poecilia reticulata<br>Daphnie - Daphnia magna<br>Daphnie - Daphnia magna<br>Algae- Pseudokirchneriella subcapitata | 96 hours<br>48 hours<br>48 hours<br>72 hours |
|                                                                      | Acute LC50 >100 mg/l*<br>NOEC > 1 mg/l                                                         | Fish - Oncorhynchus mykiss<br>Daphnie - Daphnia magna                                                                      | 96 hours<br>21 days                          |

\* According to GHS 2009 and CLP regulation 1272/2008/EC this mixture does not meet with aquatic classification and labelling criteria (regulation 1272/2008/EC Article 6 1, data generated in accordance with any of the methods referred to, in Article 8(3), on the mixture itself "NOVINOX ACE 20", and GHS 2009 chapter 1.3.2.3 a)).

### 12.2 Persistence and degradability

| Product/ingredient name                                              | Result           |
|----------------------------------------------------------------------|------------------|
| xylene (mixture of isomers)                                          | 87,8 % - 28 days |
| ethylbenzene                                                         | >70 % - 28 days  |
| solvent naphtha (petroleum), light arom.                             | 78 % - 28 days   |
| hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics | 80 % - 28 days   |
| 2-pentanone oxime                                                    | 9% - 28 days     |

Remarks: The mixture is, according to the desired resistance, not readily biodegradable.

### 12.3 Bioaccumulative potential

| Product/ingredient name                                              | LogPow             | BCF                | Potential |
|----------------------------------------------------------------------|--------------------|--------------------|-----------|
| xylene (mixture of isomers)                                          | 3.16               | 8.1 - 25.9         | low       |
| ethylbenzene                                                         | 3.6                | -                  | low       |
| solvent naphtha (petroleum), light arom.                             | 3.7 bis 4.5        | 10 - 2500          | high      |
| hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics | 5 bis 6.7          | -                  | high      |
| 2-pentanone oxime                                                    | No data available. | No data available. | yes       |
| trizinc bis(orthophosphate)                                          | -                  | 60960              | high      |

# SAFETY DATA SHEET

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II



Product name: Rostprimer B38  
Date of printing: 14.11.2025

## 12.4 Mobility in soil

Soil/water partition coefficient (KOC): Not available.

## 12.5 Results of PBT and vPvB assessment

| Product/ingredient name                                                               | PBT | P | B | T | vPvB | vP | vB |
|---------------------------------------------------------------------------------------|-----|---|---|---|------|----|----|
| This mixture does not contain any substances that are assessed to be a PBT or a vPvB. |     |   |   |   |      |    |    |

## 12.6 Endocrine disrupting properties

See Section 2 for details.

## 12.7 Other adverse effects

No known significant effects or critical hazards.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods



The generation of waste should be avoided or minimised wherever possible. Residues of the product is listed as hazardous waste. Dispose of according to all state and local applicable regulations. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Spillage, remains, discarded clothes and similar should be discarded in a fireproof container.

European waste catalogue no. (EWC) is given below.

European waste catalogue (EWC): 08 01 11\*

### Packaging

The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

## SECTION 14: Transport information

Transport may take place according to national regulation or ADR for transport by road, RID for transport by train, IMDG for transport by sea, IATA for transport by air.

|                  | 14.1<br>UN no. | 14.2<br>Proper shipping name | 14.3<br>Transport hazard class(es)                                                       | 14.4<br>PG* | 14.5<br>Env*<br>Additional information     |
|------------------|----------------|------------------------------|------------------------------------------------------------------------------------------|-------------|--------------------------------------------|
| ADR/RID<br>Class | UN1263         | PAINT                        | 3<br> | III         | No. <u>Tunnel code</u> (D/E)               |
| IMDG<br>Class    | UN1263         | PAINT                        | 3<br> | III         | No. <u>Emergency schedules</u><br>F-E, S-E |
| IATA<br>Class    | UN1263         | Paint                        | 3<br> | III         | No. -                                      |

PG\*.: Packing group

Env.\* : Environmental hazards

### 14.6 Special precautions for user

Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

### 14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not applicable.

# SAFETY DATA SHEET

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II

Product name: Rostprimer B38  
Date of printing: 14.11.2025



## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU Regulation

Regulation (EG) Nr. 1907/2006 (REACH)

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), with supplements.

Regulation (EG) Nr. 1272/2008 (CLP)

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labeling and packaging of substances and mixtures (CLP), with supplements.

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Substances of very high concern

Substances mentioned on the so-called "candidate list of substances of very high concern (SVHC) for authorisation" published by the ECHA are not intentionally added to this product. Therefore it is not expected, that these substances are present in amounts of  $\geq 0,1\%$  in this product.

#### National legislation (Germany)

**Water hazard class:** WGK 2 (Assessment by list): hazardous for water.

**VOC:** 380 g/l DIN ISO 11890 (Council Directive 1999/13/EC).

**Information about limitation of use:** Employment restrictions concerning young persons must be observed.

### 15.2 Chemical Safety Assessment

This product contains substances for which Chemical Safety Assessments are still required.

## SECTION 16: Other information

#### Abbreviations and acronyms:

| Abbr.  | Descriptions of used abbreviations                                                                                                                                              |
|--------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ADR    | Accord européen relatif au transport international des marchandises dangereuses par route (European Agreement concerning the International Carriage of Dangerous Goods by Road) |
| BCF    | bioconcentration factor                                                                                                                                                         |
| CAS    | Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)                                                                          |
| CLP    | Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures                                                                              |
| CMR    | Carcinogenic, Mutagenic or toxic for Reproduction                                                                                                                               |
| DGR    | Dangerous Goods Regulations (see IATA/DGR)                                                                                                                                      |
| DMEL   | Derived Minimal Effect Level                                                                                                                                                    |
| DNEL   | Derived No-Effect Level                                                                                                                                                         |
| EINECS | European Inventory of Existing Commercial Chemical Substances                                                                                                                   |
| ELINCS | European List of Notified Chemical Substances                                                                                                                                   |
| EmS    | Emergency Schedule                                                                                                                                                              |
| GHS    | "Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations                                                                       |
| IATA   | International Air Transport Association                                                                                                                                         |
| IMDG   | International Maritime Dangerous Goods Code                                                                                                                                     |
| IOELV  | indicative occupational exposure limit value                                                                                                                                    |
| MARPOL | International Convention for the Prevention of Pollution from Ships (abbr. of "Marine Pollutant")                                                                               |
| PBT    | Persistent, Bioaccumulative and Toxic                                                                                                                                           |
| PNEC   | Predicted No-Effect Concentration                                                                                                                                               |
| ppm    | parts per million                                                                                                                                                               |

# SAFETY DATA SHEET

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II



Product name: Rostprimer B38  
Date of printing: 14.11.2025

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals  
RID Règlement concernant le transport International ferroviaire des marchandises Dangereuses (Regulations concerning the International carriage of Dangerous goods by Rail)  
STEL short-term exposure limit  
TWA time-weighted average  
VOC Volatile Organic Compounds  
vPvB very Persistent and very Bioaccumulative

## Full text of classifications [CLP/GHS]:

Acute Tox. 4, H312 ACUTE TOXICITY (dermal) - Category 4  
Acute Tox. 4, H332 ACUTE TOXICITY (inhalation) - Category 4  
Aquatic Chronic 2, H411 LONG-TERM AQUATIC HAZARD - Category 2  
Asp. Tox. 1, H304 ASPIRATION HAZARD - Category 1  
Carc. 2, H351 CARCINOGENICITY - Category 2  
Eye Irrit. 2, H319 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2  
Flam. Liq. 3, H225 FLAMMABLE LIQUIDS - Category 2  
Flam. Liq. 3, H226 FLAMMABLE LIQUIDS - Category 3  
Skin Irrit. 2, H315 SKIN CORROSION/IRRITATION - Category 2  
Skin Sens. 1, H317 SKIN SENSITIZATION - Category 1  
STOT RE 2, H373 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2  
STOT RE 2, H373 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) (hearing organs) - Category 2  
STOT SE 3, H335 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3  
STOT SE 3, H336 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3

## Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

| Classification                                               | Justification                                                     |
|--------------------------------------------------------------|-------------------------------------------------------------------|
| Flam. Liq. 3, H226<br>Skin Irrit. 2, H315<br>STOT SE 3, H336 | On basis of test data<br>Calculation method<br>Calculation method |


## Notice to reader

*The information contained in this safety data sheet is based on the present state of knowledge and EU and national legislation. It provides guidance on health, safety and environmental aspects for handling the product in a safe way and should not be construed as any guarantee of the technical performance or suitability for particular applications. It is always the duty of the user/employer to ascertain that the work is planned and carried out in accordance with the national regulations.*

# Annex to the extended Safety Data Sheet (eSDS)

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II

Product name: Rostprimer B38  
Date of printing: 14.11.2025



**xylene, mixture of isomers**

## Annex: Exposure scenario 1

### SECTION 1: Title section

**Short title of the exposure scenario** Formulation & (re)packing of substances and mixtures (Industrial)

**Sector of Use** SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

#### Process category

PROC1 Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions.

PROC2 Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions

PROC3 Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition

PROC4 Chemical production where opportunity for exposure arises

PROC5 Mixing or blending in batch processes

PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities

PROC8b Transfer of substance or mixture (charging and discharging) at dedicated facilities

PROC9 Transfer of substance or mixture into small containers (dedicated filling line, including weighing)

PROC14 Tableting, compression, extrusion, pelletisation, granulation

PROC15 Use as laboratory reagent

**Environmental release category** ERC2 Formulation into mixture

#### Description of the activities / processes covered in the Exposure Scenario

Formulation, packing and re-packing of the substance and its mixtures in batch or continuous operations, including storage, materials transfers, mixing, tableting, compression, pelletisation, extrusion, large and small scale packing, sampling, maintenance and associated laboratory activities.

### SECTION 2: Conditions of use affecting exposure

The usual precautionary measures should be adhered to in handling the chemicals.

**Duration and frequency** 8hrs (full working shift).

#### Worker

Frequency of use:

5 workdays/week.

#### Physical parameters

##### Physical state

Fluid

Vapour pressure: 0.5-10 kPa (20 °C)

**Concentration of the substance in the mixture** Covers use of substance / product up to 100%

#### Used amount per time or activity

Regional use tonnage (tonnes/year): 15000, SU3

Annual site tonnage (tonnes/year): 3750, SU3

Maximum daily site tonnage (kg/day): 12500, SU3

#### Other operational conditions

Emission days / year: 300

Assumes use at not more than 20°C above ambient temperature (unless stated differently).

Assumes a good basic standard of occupational hygiene is implemented.

#### Other operational conditions affecting environmental exposure

Local freshwater dilution factor: 10

Local marine water dilution factor: 100

Release fraction to air from process (initial release prior to RMM) / wide dispersive use (regional only): 1 %.

Release fraction to wastewater from process (initial release prior to RMM) / wide dispersive use: 0.2 %.

Release fraction to soil from process (initial release prior to RMM) / wide dispersive use (regional only): 0.01 %.

# Annex to the extended Safety Data Sheet (eSDS)

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II



Product name: Rostprimer B38

Date of printing: 14.11.2025

## **Other operational conditions affecting worker exposure**

Clean working place and equipment every day. Avoid splashing. Remove spilled product immediately.

Keep container tightly closed in a cool place.

Avoid contact with the skin and eyes.

## **Other operational conditions affecting consumer exposure during the use of the product**

Not applicable.

**Risk management measures** Ensure that personal protective measures are used at all activities.

## **Worker protection**

Storage (PROC1 / PROC2):

Store substance within a closed system.

General exposures / Use (closed systems) PROC1 / PROC2 / PROC3:

Laboratory activities (PROC15):

No other specific measures identified.

Batch processes at elevated temperatures. Operation is carried out at elevated temperature (> 20°C above ambient temperature) PROC3:

Store / Handle product in closed systems.

Provide extract ventilation to points where emissions (can) occur.

Preparation of material for application. Use in contained batch (PROC3):

General exposures / Use (open systems) PROC4:

Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).

Process sampling (PROC3):

Provide a good standard of general ventilation.

Avoid carrying out activities involving exposure for more than 1 hour(s).

Mixing operations (open systems) PROC5:

Material transfers Drum/Batch transfer (Non-dedicated facility) PROC8a:

Material transfers Drum/batch transfers (Non-dedicated facility) PROC8b:

Material transfers Drum/batch transfers (dedicated facility) PROC8b:

Filling of drums and small containers (PROC 9):

Production or preparation of articles by tableting, compression, extrusion or pelletisation (PROC14):

Provide a good standard of general or controlled ventilation (10 to 15 air changes per hour).

Bulk transfers (closed systems) PROC8b:

Ensure that material transfer is avoided or provide extract ventilation. Use local exhaust at places where emission can occur.

Equipment cleaning and maintenance (PROC 8a, 8b):

Drain or remove substance from equipment prior to break-in or maintenance.

Retain drain downs in sealed storage pending disposal or for subsequent recycle.

## **Organisational protective measures**

Ensure good ventilation. This can be achieved by using a local exhaust or general exhaust system. If these measures are insufficient to keep the solvent vapour concentration below the workplace limit, wear an adequate respiratory protective device.

The employer must ensure that the necessary personal protective devices are available and applied accordingly to the instructions.

## **Technical protective measures**

Provide explosion-proof electrical equipment.

Ensure that suitable extractors are available on processing machines

## **Personal protective measures**

Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop.

Do not inhale gases / fumes / aerosols.

Safety glasses

**Measures for consumer protection** Not relevant for this Exposure Scenario.

## **Environmental protection measures**

### **Air**

Treatment of air emissions is not required for the purposes of REACH compliance but may be needed to comply with other environmental legislation.

Treat air emission to provide a typical removal efficiency of (%): 0

# Annex to the extended Safety Data Sheet (eSDS)

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II

Product name: Rostprimer B38  
Date of printing: 14.11.2025



## Water

*Sludge treatment: Incineration or in a landfill*

*Prevent discharge of undissolved substance to or recover from onsite wastewater.*

*Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%): 93.6*

*Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/day): 6.31*

*Assumed domestic sewage treatment plant flow (m3/d): 2000*

**Soil** *Use bunds or dykes around storage facilities to prevent soil and water pollution in the event of a spill.*

## Disposal measures

*External treatment and disposal of waste should comply with applicable local and/or national regulations.*

*External recovery and recycling of waste should comply with applicable local and/or national regulations.*

**Waste type** *Partially emptied and uncleaned packaging*

**Notes** *Disposal must be made according to official regulations.*

## SECTION 3: Exposure estimation

**Worker (oral)** *No significant oral exposure.*

### Worker (dermal)

PROC 1 / 3 / 15:

*Exposure estimate: 0.34 mg/kg/day*

*RCR: 0*

PROC 2:

*Exposure estimate: 1.37 mg/kg/day*

*RCR: 0.01*

PROC 4 / 8b / 9:

*Exposure estimate: 6.86 mg/kg/day*

*RCR: 0.04*

PROC 5 / 8a:

*Exposure estimate: 13.71 mg/kg/day*

*RCR: 0.04*

PROC 14:

*Exposure estimate: 3.43 mg/kg/day*

*RCR: 0.02*

### Worker (inhalation)

PROC 1:

*Exposure estimate: 0.01 ppm*

*RCR: 0*

PROC 2 / 15:

*Exposure estimate: 10 ppm*

*RCR: 0.56*

PROC 3:

*Exposure estimate: 17.5 ppm*

*RCR: 0.99*

PROC 4:

*Exposure estimate: 14 ppm*

*RCR: 0.79*

PROC 5 / 8a / 8b / 9 / 14:

*Exposure estimate: 15 ppm*

*RCR: 0.85*

**Environment** *The calculated value is smaller than the PNEC.*

**Consumer** *Not relevant for this Exposure Scenario.*

# Annex to the extended Safety Data Sheet (eSDS)

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II

Product name: Rostprimer B38  
Date of printing: 14.11.2025



## **SECTION 4: Guidance for downstream users**

*The exposure estimation was carried out in accordance with ECETOC TRA.*

*Version 3. <http://www.ecetoc.org/tra>*

*Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/ Operational Conditions outlined in Section 2 are implemented. Where other Risk Management Measures/ Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.*

*Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.*

*Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.*

*Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.*

# Annex to the extended Safety Data Sheet (eSDS)

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II

Product name: Rostprimer B38

Date of printing: 14.11.2025



## Annex: Exposure scenario 2

### SECTION 1: Title section

**Short title of the exposure scenario** Uses in Coatings - Industrial

**Sector of Use** SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

#### Process category

PROC1 Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions.

PROC2 Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions

PROC3 Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition

PROC4 Chemical production where opportunity for exposure arises

PROC5 Mixing or blending in batch processes

PROC7 Industrial spraying

PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities

PROC8b Transfer of substance or mixture (charging and discharging) at dedicated facilities

PROC9 Transfer of substance or mixture into small containers (dedicated filling line, including weighing)

PROC10 Roller application or brushing

PROC13 Treatment of articles by dipping and pouring

PROC14 Tableting, compression, extrusion, pelletisation, granulation

PROC15 Use as laboratory reagent

#### Environmental release category

ERC4 Use of non-reactive processing aid at industrial site (no inclusion into or onto article)

#### Description of the activities / processes covered in the Exposure Scenario

Covers the use in coatings (paints, inks, adhesives, etc) including exposures during use (including materials receipt, storage, preparation and transfer from bulk and semi-bulk, application by spray, roller, spreader, dip, flow, fluidised bed on production lines and film formation) and equipment cleaning, maintenance and associated laboratory activities.

### SECTION 2: Conditions of use affecting exposure

The usual precautionary measures should be adhered to in handling the chemicals.

**Duration and frequency** 8hrs (full working shift).

#### Worker

Frequency of use:

5 workdays/week.

#### Physical parameters

##### Physical state

Fluid

Vapour pressure: 0.5-10 kPa (20 °C)

**Concentration of the substance in the mixture** Covers use of substance / product up to 100%

#### Used amount per time or activity

Regional use tonnage (tonnes/year): 5000, SU3

Annual site tonnage (tonnes/year): 5000, SU3

Maximum daily site tonnage (kg/day): 17000, SU3

#### Other operational conditions

Continuous release.

Emissiondays /year: 300

Assumes use at not more than 20°C above ambient temperature (unless stated differently).

Assumes a good basic standard of occupational hygiene is implemented.

#### Other operational conditions affecting environmental exposure

Local freshwater dilution factor: 10

Local marine water dilution factor: 100

Release fraction to air from process (initial release prior to RMM) / wide dispersive use (regional only): 98 %.

# Annex to the extended Safety Data Sheet (eSDS)

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II

Product name: Rostprimer B38  
Date of printing: 14.11.2025



Release fraction to wastewater from process (initial release prior to RMM) / wide dispersive use: 0.7 %.  
Release fraction to soil from process (initial release prior to RMM) / wide dispersive use (regional only): 0 %.

## **Other operational conditions affecting worker exposure**

Clean working place and equipment every day. Avoid splashing. Remove spilled product immediately.  
Keep container tightly closed in a cool place.  
Avoid contact with the skin and eyes.

## **Other operational conditions affecting consumer exposure during the use of the product**

Not applicable.

## **Risk management measures**

Ensure that personal protective measures are used at all activities.  
Other skin protection measures such as impervious suits and face shields may be required during high dispersion activities which are likely to lead to substantial aerosol release, e.g. spraying.

## **Worker protection**

Storage (PROC1 / PROC2):

Store substance within a closed system.

General exposures / Use (closed systems) PROC1 / PROC2 / PROC3:

Laboratory activities (PROC15):

No other specific measures identified.

Film formation - force drying, stoving and other technologies (closed systems).

Operation is carried out at elevated temperature (> 20°C above ambient temperature) PROC2:

Store / Handle product in closed systems.

Provide extract ventilation to points where emissions (can) occur.

Mixing operations (closed systems) PROC:

Film formation - air drying (PROC4):

Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).

Preparation of material for application (PROC5):

Provide a good standard of general or controlled ventilation (5 to 15 air changes per hour).

Avoid manual contact with wet work pieces.

Transfer from/pouring from containers (PROC8a,8b,9):

Apply by Rolling or Brushing (PROC10):

Treatment by dipping and pouring (PROC13):

Production or preparation of articles by tableting, compression, extrusion or pelletisation (PROC14):

Provide a good standard of general or controlled ventilation (10 to 15 air changes per hour).

Material transfers Drum/Batch transfer (Non-dedicated facility) PROC8a:

Material transfers Drum/batch transfers (Non-dedicated facility) PROC8b:

Material transfers Drum/batch transfers (dedicated facility) PROC8b:

Ensure that material transfer is avoided or provide extract ventilation.

Spraying (automatic/robotic) PROC7:

Carry out in a vented booth or extracted enclosure.

Spraying (PROC 7 (manuell)):

Provide a good standard of general or controlled ventilation (10 to 15 air changes per hour).

Wear a respirator conforming to EN140 with Type A filter or better.

Equipment cleaning and maintenance (Non-dedicated facility) PROC 8a:

Drain or remove substance from equipment prior to break-in or maintenance.

## **Organisational protective measures**

Ensure good ventilation. This can be achieved by using a local exhaust or general exhaust system. If these measures are insufficient to keep the solvent vapour concentration below the workplace limit, wear an adequate respiratory protective device.


The employer must ensure that the necessary personal protective devices are available and applied accordingly to the instructions.

# Annex to the extended Safety Data Sheet (eSDS)

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II

Product name: Rostprimer B38

Date of printing: 14.11.2025



## Technical protective measures

Provide explosion-proof electrical equipment.

Ensure that suitable extractors are available on processing machines

## Personal protective measures

Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop.

Do not inhale gases / fumes / aerosols.

Safety glasses

**Measures for consumer protection** Not relevant for this Exposure Scenario.

## Environmental protection measures

### Air

Treatment of air emissions is not required for the purposes of REACH compliance but may be needed to comply with other environmental legislation.

Treat air emission to provide a typical removal efficiency of (%): 90

### Water

Sludge treatment: Incineration or in a landfill

Prevent discharge of undissolved substance to or recover from onsite wastewater.

Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%): 93.6

Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/day): 69000

Assumed domestic sewage treatment plant flow (m3/d): 2000

**Soil** Use bunds or dykes around storage facilities to prevent soil and water pollution in the event of a spill.

**Notes** In case of unintended release of the product: See section 6 of the Safety Data Sheet.

## Disposal measures

External treatment and disposal of waste should comply with applicable local and/or national regulations.

External recovery and recycling of waste should comply with applicable local and/or national regulations.

**Waste type** Partially emptied and uncleaned packaging

**Notes** Disposal must be made according to official regulations.

## SECTION 3: Exposure estimation

**Worker (oral)** No significant oral exposure.

**Worker (dermal)**

PROC 1 / 3 / 15:

Exposure estimate: 0.34 mg/kg/day

RCR: 0

PROC 2 / 8a:

Exposure estimate: 1.37 mg/kg/day

RCR: 0.01

PROC 4 / 13:

Exposure estimate: 13.71 mg/kg/day

RCR: 0.08

PROC 5:

Exposure estimate: 0.07 mg/kg/day

RCR: 0

PROC 7 (automatisch):

Exposure estimate: 2.14 mg/kg/day

RCR: 0.01

PROC 7 (manuell):

Exposure estimate: 42.86 mg/kg/day

RCR: 0.24

PROC 8a (Anlagenr.):

Exposure estimate: 0.69 mg/kg/day

RCR: 0

# Annex to the extended Safety Data Sheet (eSDS)

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II

Product name: Rostprimer B38  
Date of printing: 14.11.2025



*PROC 8b / 9:*

*Exposure estimate: 6.86 mg/kg/day*

*RCR: 0.04*

*PROC 10:*

*Exposure estimate: 27.43 mg/kg/day*

*RCR: 0.15*

*PROC 14:*

*Exposure estimate: 3.43 mg/kg/day*

*RCR: 0.02*

## **Worker (inhalation)**

*PROC 1:*

*Exposure estimate: 0.01 ppm*

*RCR: 0*

*PROC 2 / 8a (Anlagenr.) / 15:*

*Exposure estimate: 10 ppm*

*RCR: 0.56*

*PROC 3:*

*Exposure estimate: 17.5 ppm*

*RCR: 0.99*

*PROC 4 / 5 / 9 / 13 / 14:*

*Exposure estimate: 15 ppm*

*RCR: 0.85*

*PROC 7 (automatisch):*

*Exposure estimate: 12.5 ppm*

*RCR: 0.71*

*PROC 7 (manuell):*

*Exposure estimate: 7.5 ppm*

*RCR: 0.42*

*PROC 8a / 10:*

*Exposure estimate: 5 ppm*

*RCR: 0.28*

*PROC 8b:*

*Exposure estimate: 1.5 ppm*

*RCR: 0.08*

**Environment** *The calculated value is smaller than the PNEC.*

**Consumer** *Not relevant for this Exposure Scenario.*

## **SECTION 4: Guidance for downstream users**

*The exposure estimation was carried out in accordance with ECETOC TRA.*

*Version 3. <http://www.ecetoc.org/tra>*

*Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/ Operational Conditions outlined in Section 2 are implemented. Where other Risk Management Measures/ Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.*

*Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.*

*Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.*

*Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.*

# Annex to the extended Safety Data Sheet (eSDS)

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II

Product name: Rostprimer B38

Date of printing: 14.11.2025



## Annex: Exposure scenario 3

### SECTION 1: Title section

**Short title of the exposure scenario** Uses in Coatings - Professional

#### Sector of Use

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

#### Process category

PROC1 Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions.

PROC2 Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions

PROC3 Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition

PROC4 Chemical production where opportunity for exposure arises

PROC5 Mixing or blending in batch processes

PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities

PROC8b Transfer of substance or mixture (charging and discharging) at dedicated facilities

PROC10 Roller application or brushing

PROC11 Non industrial spraying

PROC13 Treatment of articles by dipping and pouring

PROC15 Use as laboratory reagent

PROC19 Manual activities involving hand contact

#### Environmental release category

ERC8a Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor)

ERC8d Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor)

#### Description of the activities / processes covered in the Exposure Scenario

Covers the use in coatings (paints, inks, adhesives, etc) including exposures during use (including materials receipt, storage, preparation and transfer from bulk and semi-bulk, application by spray, roller, spreader, dip, flow, fluidised bed on production lines and film formation) and equipment cleaning, maintenance and associated laboratory activities.

### SECTION 2: Conditions of use affecting exposure

The usual precautionary measures should be adhered to in handling the chemicals.

**Duration and frequency** 8hrs (full working shift).

#### Worker

Frequency of use:

5 workdays/week.

#### Physical parameters

##### Physical state

Fluid

Vapour pressure: 0.5-10 kPa (20 °C)

#### Concentration of the substance in the mixture

Covers use of substance / product up to 100% (unless stated otherwise).

#### Used amount per time or activity

Regional use tonnage (tonnes/year): 5000, SU22

Annual site tonnage (tonnes/year): 10, SU22

Maximum daily site tonnage (kg/day): 27.4, SU22

#### Other operational conditions

Continuous release.

Emissiondays /year: 365

Assumes use at not more than 20°C above ambient temperature (unless stated differently).

Assumes a good basic standard of occupational hygiene is implemented.

#### Other operational conditions affecting environmental exposure

Local freshwater dilution factor: 10

Local marine water dilution factor: 100

# Annex to the extended Safety Data Sheet (eSDS)

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II



Product name: Rostprimer B38

Date of printing: 14.11.2025

Release fraction to air from process (initial release prior to RMM) / wide dispersive use (regional only): 98 %.

Release fraction to wastewater from process (initial release prior to RMM) / wide dispersive use: 1 %.

Release fraction to soil from process (initial release prior to RMM) / wide dispersive use (regional only): 1 %.

## **Other operational conditions affecting worker exposure**

Clean working place and equipment every day. Avoid splashing. Remove spilled product immediately.

Keep container tightly closed in a cool place.

Avoid contact with the skin and eyes.

## **Other operational conditions affecting consumer exposure during the use of the product**

Not applicable.

## **Risk management measures**

Ensure that personal protective measures are used at all activities.

Other skin protection measures such as impervious suits and face shields may be required during high dispersion activities which are likely to lead to substantial aerosol release, e.g. spraying.

## **Worker protection**

Storage (PROC1 / PROC2):

Store substance within a closed system.

General exposures / Use (closed systems) PROC1 / PROC2 / PROC3:

Filling / preparation of equipment from drums or containers (Use in closed systems) PROC2:

Ensure material transfers are under containment or extract ventilation.

Preparation of material for application. Use in contained batch (PROC3):

Provide a good standard of general or controlled ventilation (5 to 15 air changes per hour).

Use drum pumps or carefully pour from container.

Film formation - air drying Indoor (PROC4):

Provide a good standard of general ventilation.

Provide extract ventilation to points where emissions (can) occur.

Avoid manual contact with wet work pieces.

Film formation - air drying Outdoors (PROC 4):

Ensure operation is undertaken outdoors. Avoid manual contact with wet work pieces. Clear spills immediately.

Avoid carrying out activities involving exposure for more than 1 hour(s).

Preparation of material for application Indoor PROC 5:

Provide a good standard of general ventilation (10 to 15 air changes per hour).

Controlled ventilation means air is supplied or removed by a powered fan.

Avoid carrying out activities involving exposure for more than 1 hour(s).

Preparation of material for application Outdoor (PROC 5):

Ensure operation is undertaken outdoors.

Avoid carrying out activities involving exposure for more than 1 hour(s).

Material transfers Drum/Batch transfer (Non-dedicated facility) PROC8a:

Material transfers Drum/batch transfers (Non-dedicated facility) PROC8b:

Material transfers Drum/batch transfers (dedicated facility) PROC8b:

Transfer via enclosed lines.

Clear transfer lines prior to de-coupling.

Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).

Equipment cleaning and maintenance (Non-dedicated facility) PROC 8a:

Drain down system prior to equipment break-in or maintenance.

Avoid carrying out activities involving exposure for more than 4 hour(s).

Provide a good standard of general or controlled ventilation (10 to 15 air changes per hour).

Roller, spreader, flow application Indoor (PROC 10):

Provide a good standard of general or controlled ventilation (10 to 15 air changes per hour).

Wear a respirator conforming to EN140 with Type A filter or better.

Roller, spreader, flow application Outdoor (PROC 10):

Dipping, immersion and pouring Outdoor (PROC 13):

Ensure Operation is undertaken outdoors. Wear a respirator conforming to EN140 with Type A filter or better. Automate activity where possible.

# Annex to the extended Safety Data Sheet (eSDS)

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II



Product name: Rostprimer B38

Date of printing: 14.11.2025

## *Spraying Manual (PROC 11):*

*Carry out in a vented booth or extracted enclosure.*

## *Spraying (PROC 11, außen):*

*Ensure operation is undertaken outdoors.*

*Avoid carrying out activities involving exposure for more than 4 hour(s).*

*Wear a respirator conforming to EN140 with Type A filter or better.*

## *Dipping, immersion and pouring Indoor (PROC 13):*

*Use local exhaust at places where emission can occur.*

*Avoid carrying out activities involving exposure for more than 4 hour(s).*

## *Laboratory activities (PROC15):*

*Handle substance within a predominantly closed system provided with extract ventilation.*

*Hand application - fingerpaints, pastels, adhesives PROC19 Indoor:*

*Provide a good standard of general or controlled ventilation (10 to 15 air changes per hour).*

*Limit the substance content in the product to 5%.*

*Hand application - fingerpaints, pastels, adhesives PROC19 Outdoor:*

*Ensure operation is undertaken outdoors.*

*Limit the substance content in the product to 5%.*

*Avoid carrying out activities involving exposure for more than 4 hour(s).*

## **Organisational protective measures**

*Ensure good ventilation. This can be achieved by using a local exhaust or general exhaust system. If these measures are insufficient to keep the solvent vapour concentration below the workplace limit, wear an adequate respiratory protective device.*

*The employer must ensure that the necessary personal protective devices are available and applied accordingly to the instructions.*

## **Technical protective measures**

*Provide explosion-proof electrical equipment.*

*Ensure that suitable extractors are available on processing machines*

## **Personal protective measures**

*Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop.*

*Do not inhale gases / fumes / aerosols.*

*Safety glasses*

**Measures for consumer protection** Not relevant for this Exposure Scenario.

## **Environmental protection measures**

### **Air**

*Treatment of air emissions is not required for the purposes of REACH compliance but may be needed to comply with other environmental legislation.*

*Treat air emission to provide a typical removal efficiency of (%): 0*

### **Water**

*Sludge treatment: Incineration or in a landfill*

*Prevent discharge of undissolved substance to or recover from onsite wastewater.*

*Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%): 93.6*

*Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/day): 4600*

*Assumed domestic sewage treatment plant flow (m3/d): 2000*

**Soil** Use bunds or dykes around storage facilities to prevent soil and water pollution in the event of a spill.

## **Disposal measures**

*External treatment and disposal of waste should comply with applicable local and/or national regulations.*

*External recovery and recycling of waste should comply with applicable local and/or national regulations.*

**Waste type** Partially emptied and uncleaned packaging

**Notes** Disposal must be made according to official regulations.

# Annex to the extended Safety Data Sheet (eSDS)

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II

Product name: Rostprimer B38

Date of printing: 14.11.2025



## SECTION 3: Exposure estimation

**Worker (oral)** No significant oral exposure.

### **Worker (dermal)**

PROC 1:

Exposure estimate: 0.34 mg/kg/day

RCR: 0

PROC 2:

Exposure estimate: 0.14 mg/kg/day

RCR: 0

PROC 3 / 15:

Exposure estimate: 0.03 mg/kg/day

RCR: 0

PROC 4 (innen) / 8b:

Exposure estimate: 6.86 mg/kg/day

RCR: 0.04

PROC 4 (außen):

Exposure estimate: 1.37 mg/kg/day

RCR: 0.01

PROC 5 / 8a:

Exposure estimate: 13.71 mg/kg/day

RCR: 0.08

PROC 10:

Exposure estimate: 27.43 mg/kg/day

RCR: 0.15

PROC 11 (innen):

Exposure estimate: 2.14 mg/kg/day

RCR: 0.01

PROC 11 (außen):

Exposure estimate: 21.43 mg/kg/day

RCR: 0.12

PROC 13:

Exposure estimate: 0.69 mg/kg/day

RCR: 0

PROC 19:

Exposure estimate: 28.29 mg/kg/day

RCR: 0.16

### **Worker (inhalation)**

PROC 1:

Exposure estimate: 0.1 ppm

RCR: 0.01

PROC 2:

Exposure estimate: 4 ppm

RCR: 0.23

PROC 3:

Exposure estimate: 7.5 ppm

RCR: 0.42

PROC 4 (innen):

Exposure estimate: 3.5 ppm

RCR: 0.2

PROC 4 + 10 + 13 (jew. außen):

Exposure estimate: 7 ppm

RCR: 0.39

PROC 5 (innen) / 19 (innen):

Exposure estimate: 6 ppm

RCR: 0.34

# Annex to the extended Safety Data Sheet (eSDS)

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II

Product name: Rostprimer B38  
Date of printing: 14.11.2025



*PROC 5 (außen) / 8a:*

*Exposure estimate: 14 ppm*

*RCR: 0.79*

*PROC 8b:*

*Exposure estimate: 15 ppm*

*RCR: 0.85*

*PROC 10 (innen):*

*Exposure estimate: 3 ppm*

*RCR: 0.17*

*PROC 11 (innen):*

*Exposure estimate: 5 ppm*

*RCR: 0.28*

*PROC 11 (außen):*

*Exposure estimate: 10.5 ppm*

*RCR: 0.59*

*PROC 13 (innen):*

*Exposure estimate: 12 ppm*

*RCR: 0.68*

*PROC 15:*

*Exposure estimate: 0.6 ppm*

*RCR: 0.03*

*PROC 19 (außen):*

*Exposure estimate: 8.4 ppm*

*RCR: 0.47*

**Environment** *The calculated value is smaller than the PNEC.*

**Consumer** *Not relevant for this Exposure Scenario.*

## **SECTION 4: Guidance for downstream users**

*The exposure estimation was carried out in accordance with ECETOC TRA.*

*Version 3. <http://www.ecetoc.org/tra>*

*Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/ Operational Conditions outlined in Section 2 are implemented. Where other Risk Management Measures/ Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.*

*Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.*

*Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.*

*Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.*